

## EX3 SMART STEAM TRADITIONAL ESPRESSO

## Versions

- EX3 MINI 2GR DISLAY TA BLACK SMART STEAM
- EX3 2GR DISPLAY TA BLACK SMART STEAM





EX3 MINI 2GR DISLAY TA BLACK SMART STEAM

The EX3 can be equipped with our well-known

solution with an integrated temperature probe to

Our SmartSteam provides a barista quality foam with any kind of milk, as temperaure and air pump can be easily adjusted. Furthermore, our SmartSteam wand design allows you to easily change the nozzle between the turbo (faster) and

the barista one (slightly slower, but performing a

SmartSteam, CREM automatic steamer wand



EX3 2GR DISLAY TA BLACK SMART STEAM




## Features

easily froth milk.

• 2x2 function lever<sup>NEW</sup>

premium quality foam).

- Push & Flush
- Two set recipes
- Adjustable temperature & foaming levels (recipes) through the group display
- Auto cleaning system: number of cycles and frequency (1-min-30min; 5 min default)
- Two different nozzles: turbo (faster) and the barista one (slightly slower, but performing a premium quality foam)
- Ergonomics and functionality very similar to a standard wand while keeping aesthetics





## Technical specifications





	EX3 DISPLAY 2GR TA Smart Steam	EX3 DISPLAY MINI 2GR TA Smart Steam
Height, width, depth	465, 770, 575 mm 18.3, 30.3, 22.6"	465, 550, 575 mm 18.3, 21.6, 22.6"
Weight	62 Kg   136.7 lb	50 Kg   110.2 lb
Power ratings (Power ratings+OPTIONS)	220-240V~ 3350W 50-60Hz (0) 3Ph: 380-415V 3N~ 4800W 50-60 Hz	220-240V~ 2800W 50-60Hz (0) 220-240V~ 2300W 50-60Hz
Boiler(s) capacity	11.5	61
Operation pressure	0.8 to 1.2 bar	0.8 to 1.2 bar
Pressure switch control	✓	✓
PID control	✓	$\checkmark$
Water connection	3/8" Internal thread	3/8" Internal thread
Height group	TA	ТА
Volumetric dosing + group display	✓	✓
Group flush button	$\checkmark$	$\checkmark$
Steam wands + HW tap	2+1	2+1
Auto hot tap water dose	✓	$\checkmark$
Lever taps	$\checkmark$	$\checkmark$
Cool touch steam wands	✓	$\checkmark$
Built-in rotatory pump	✓	$\checkmark$
Pre infusion chamber group head	✓	$\checkmark$
Electronic pre infusion	✓	$\checkmark$
Jet hole	TA group: 2.5 mm	TA group: 2.5 mm
Pressure gauge	60 mm single	60 mm single
Colours	Black	Black
Levers finishing	Black	Black
Body covers	O: Oak, walnut, aluminium	O: Oak, walnut, aluminium
Barista lights	✓	$\checkmark$
Auto cleaning group cycle	4	$\checkmark$
ECO mode	$\checkmark$	$\checkmark$
Auto On/OFF	✓	$\checkmark$
Power cord (Country Kit)	STD: Type F (1Ph) or BareW (3Ph)O: Only for 1Ph (Type I 15A, 16A BareW)	STD: Type F O: Only for 1Ph (Type I 10A, Type G 13A)
Single+Double portafilter	1+2	1+2

NOTE: Please check your regional price list for available versions/options and part numbers. **INSTALLATION NOTE:** Please refer to the User Manual and the Technical Manual.



MCI (Material Ciruclarity Indicator) = 0,65 80% Recycable material 30% Recycle material used in feedstock 07



CREM reserves the right to make changes to the design or specifications without prior notice.